



Art.-No.: 6.1126.1850 6.1126.1005
 6.1126.2450
 6.1126.3050
 6.1126.3650
 6.1126.4850

1126

Masking Tape 80°

Characteristics

Masking Tape for automotive repair workshops. Also suitable for wall-painting on building and construction sites, industrial and car repair applications.

- Good adhesion even on irregular surfaces
- Heat resistant up to 80°C (30 minutes)
- Easy removal without adhesive residue as soon as paint is dry
- Well conformable to most shaped surfaces
- Compatible with most common paints and lacquers
- Removable without breaking
- Hand tearable

Tech Tip

Working temperature of the adhesive tape should be at least 15 ° C.

For water-based paints only partially suitable.

Remove within 48 hours.

Sizes

1126.1850 - 18mm x 50m

1126.2450 - 24mm x 50m

1126.3050 - 30mm x 50m

1126.3650 - 36mm x 50m

1126.4850 - 48mm x 50m

1126.1005 - 100mm x 50m

Technical Data

| | |
|---------------------|---|
| Backing | 58 g/m ² natural white saturated crepe paper |
| Adhesive | Dry natural rubber and resins solvent based |
| Total thickness | 0.125 mm |
| Adhesion to steel | 4.3 N/25mm |
| Tensile strength MD | 85 N/25mm |
| Elongation at break | 7.5 % |
| Temp. resistance | 80°C (30 min) |

Storage and Transportation

12 months shelf life - recommended storage temperature is between 15 ° C and 25 ° C at max. relative humidity of 65%. The material should be kept away from sources of heat and, if possible, kept in its original packaging, avoiding exposure to light. If the temperature is below the recommended temperature, the adhesive tape must always be brought to normal temperature before use.

