



Art.-No.: 6.1131.1850
 6.1131.2450
 6.1131.3050
 6.1131.3650
 6.1131.4850

1131

Masking Tape 90° WP

Characteristics

Waterproof premium masking tape for car repair shops and paint shops as well as for applications with high temperature resistance.

- Good adhesion even on uneven surfaces
- Heat resistant up to 90 ° C (30 minutes)
- Easy removal without adhesive residue
- Adaptable to most shaped surfaces
- Compatible with all common colors and paints
- Removable without tearing
- Resistant to moisture and water

Tech Tip

The tape should be at least 15 ° C before processing.

Sizes

1131.1850 - 18mm x 50m

1131.2450 - 24mm x 50m

1131.3050 - 30mm x 50m

1131.3650 - 36mm x 50m

1131.4850 - 48mm x 50m

Technical Data

Backing	61 g/m ² waterproofed green crepe paper
Adhesive	Dry natural rubber based
Total thickness	0.13 mm
Adhesion to steel	4.8 N/25mm
Tensile strength MD	87.5 N/25mm
Elongation at break	8 %
Temp. Resistance	90°C (30 min)

Storage and Transportation

12 months shelf life - recommended storage temperature is between 15 ° C and 25 ° C at max. relative humidity of 65%. The material should be kept away from sources of heat and, if possible, kept in its original packaging, avoiding exposure to light. If the temperature is below the recommended temperature, the adhesive tape must always be brought to normal temperature before use.

