



Art.-No.: 6.1140.1850  
 6.1140.2450  
 6.1140.3050  
 6.1140.3650  
 6.1140.4850

**1140**

## Trillennium Masking Tape

### Characteristics

Masking tape of the latest generation. Safest masking in all painting work. Excellent adhesive power, especially suitable for bonding heavy masking paper. Also suitable for bonding to difficult substrates such as plastic, rubber or silicone. Waterproof and IR resistant. Heat resistant up to 120 ° C.

- Good adhesion even on uneven surfaces
- Heat resistant up to 120 ° C
- Adaptable to most shaped surfaces
- Compatible with all common colors and paints
- Removable without tearing
- Resistant to moisture and water

### Tech Tip

Adhesive tape should be at least 15 ° C before processing.

### Technical Data

Backing	Coarse crepe paper
Colour	Dark blue
Adhesive	Rubber / Resin
Adhesion to steel	26 (7.1 N/25mm)
Quick stick to kraft	5 (1.4 N/25mm)
Quick Stick to steel	12 (3.3 N/25mm)
Tensile strength	23 (101 N/25mm)
Elongation	7.5 % at break
Thickness	6.7 mils (0.17mm)

### Storage and Transportation

12 months shelf life - recommended storage temperature is between 15 ° C and 25 ° C at max. relative humidity of 65%. The material should be kept away from sources of heat and, if possible, kept in its original packaging, avoiding exposure to light. If the temperature is below the recommended temperature, the adhesive tape must always be brought to normal temperature before use.

