Technical Data Sheet Revised: 2020-03-23 | 1/1



Art.-No.: 6.1141.1850

1141

## **Masking Tape Orange**

## Characteristics

Extra thin masking tape for multicolour and design finishes, especially suitable for covering plastic parts and disc rubbers. Significant reduction of paint edges. High cornering stability and waterproof. Temperature resistant up to 100  $^\circ$  C.

- Good adhesion even on uneven surfaces
- Heat resistant up to 100  $^{\circ}$  C
- Easy removal without adhesive residue
- Adaptable to most shaped surfaces
- Compatible with all common colors and paints
- Removable without tearing
- Resistant to moisture and water



Adhesive tape should be at least 15 ° C before processing.

## Technical Data

Base material Japanese paper

Adhesive Acrylic
Tensile strength 29.0 N/10mm
Adhesion to steel 1.55 N/10mm
Total thickness 0,085 mm
Elongation at break 6 %

 $\begin{array}{ll} \mbox{Holding power} & 1.0 \mbox{ Shear/mm} \\ \mbox{Heat resistance} & \mbox{up to } 100\mbox{°C} \end{array}$ 



12 months shelf life - recommended storage temperature is between 15  $^{\circ}$  C and 25  $^{\circ}$  C at max. relative humidity of 65%. The material should be kept away from sources of heat and, if possible, kept in its original packaging, avoiding exposure to light. If the temperature is below the recommended temperature, the adhesive tape must always be brought to normal temperature before use.

