



Art.-No.: 6.1150.4300
6.1150.4151
6.1150.4815

1150

Masking Plastic Profi WP

Characteristics

WP cover film for quick and safe covering of vehicles and vehicle parts with residual moisture. The special surface finish of the film protects against moisture spots when drying in the spray booth.

- static
- paint-adhesive
- infrared resistant
- slightly transparent
- hard-wearing
- temperature resistance up to 110 ° C

Tech Tip

The special surface finish of the film protects against moisture spots on the surface (ghost mapping) when drying in the spray booth.

Sizes

1150.4300 - 4 m x 300 m (not WP)

1150.4151 - 4 m x 150 m, WP

1150.4815 - 4.8 m x 150 m, WP

Technical Data

Colour	Orange
Density	ca. 0,95 g/cm ²
Tensile strength	31,4 N/mm ² (machine direction)
Tensile strength	24,9 N/mm ² (transverse direction)
Elongation at break	500 % (machine direction)
Elongation at break	580 % (transverse direction)
Dart drop	7,37 g/μm
Temperature stability	110°C
Dimension	4 m x 300 m
Thickness	15 μm

Storage and Transportation

12 months storage time.
Storage temperature: + 20°C / ± 10°C
Relative humidity (RH): 30 - 90 %
Storage: in closed rooms and away from sources of sunlight

