



Art.-No.: 6.1180.2514

**1180**

## Striping Tape

### Characteristics

Pre-cut flexible color line tape for decorative strips.

Eight strips of 1.5mm width which allows different widths or multiple strips.

Temperature resistant up to 138 °C for a maximum of 45 minutes.

1180 can be removed without glue residue and guarantees clean and accurate parting lines.

1180 adheres to a variety of different surfaces



### Application

1. Apply the Striping Tape to the part to be painted with light pressure.
2. Determine the desired stripe pattern and remove the corresponding stripes.
3. Cover well not to be painted areas.
4. Paint the desired color.
5. Remove the Striping Tape after drying.

### Technical Data

Carrier	Embossed Polypropylene
Colour	Olive green
Width	25mm (+/- 1mm)
Length	14m (+/- 0.1m)
Thickness	0.127mm PSTC-33
Adhesive	Pigmented Urethane Pressure Sensitive Adhesive
Tensile Strength	0.215 kg/mm ASTM D-3759
Elongation at Break	600%
Adhesion to Steel	33.6 g/mm ASTM D-3330
Heat Resistance	138°C Maximum for 45 minutes

### Storage and Transportation

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.