



Art.-No.:6.3600.0001  
 6.3600.0002  
 6.3600.0003  
 6.3600.0004

**3600**

## Soft Pad 140 x 115 mm

### Characteristics

Places with limited access, such as door handle depressions, bumpers and radiator grilles, are the ideal fields of application for the Soft Pad. In contrast with emery paper, the Soft Pad can be folded without buckling. This prevents damage to the varnish. The texture of the Soft Pad is matched in an optimum way to customer requirements and also produces a perfect surface in the finest grits.

### Tech Tip

- Perfect surface finishes, thanks to pressure-distributing foam
- No sanding-through of varnish due to excessive compressive force
- Perfect adaptation to the workpiece
- Can be used wet or dry

### Application

- Keying of works priming coats
- Keying of plastics before filler application (medium)
- Final filler sanding at places with limited access (fine)
- Mat finishing of varnishes (super fine)
- Mat finishing of critical varnishes (ultra fine)

### Grit range

Medium - P 60 - corresponds approx. to surface quality P 280  
 Fine - P 100 - corresponds approx. to surface quality P 500 - 600  
 Super fine - P 180 - corresponds approx. to surface quality P 1000  
 Ultra fine - P 280 - corresponds approx. to surface quality P 1500

### Technical Data

Dimensions	115 mm x 140 mm x 5 mm (w x l x d)
Coating	1-sided
Grit	white aluminium oxide
Backing material	EVA foam (ethyl vinyl acetate)
Foam hardness	soft, for optimum adaptation