according to 1907/2006/EC, Article 31

**CR** 

Revision: 07.09.2018

Printing date 07.09.2018

Version number 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

4CR Vertriebsgesellschaft mbH Oberer Sommerfeldweg 2

D-94469 Deggendorf

Tel.: +49 (0) 40 69 60 99 315 Fax: +49 (0) 40 69 60 99 316 E-Mail: Info@4CR.com

www.4CR.com

• 1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

# SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Hexamethylene diisocyanate, oligomers

butyl acetate

2-ethoxy-1-methylethyl acetate

dibutyltin dilaurate

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)

according to 1907/2006/EC, Article 31



Revision: 07.09.2018

Printing date 07.09.2018

Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

(Contd. of page 1)

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
Γ	CAS: 28182-81-2	Hexamethylene diisocyanate, oligomers	50-100%
	NLP: 500-060-2 Reg.nr.: 01-2119485796-17 01-2119488934-20	• Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	
	CAS: 123-86-4	butyl acetate	25-50%
	EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	♠ Flam. Liq. 3, H226; ♠ STOT SE 3, H336	
	CAS: 54839-24-6	2-ethoxy-1-methylethyl acetate	10-25%
	EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	♠ Flam. Liq. 3, H226; ♠ STOT SE 3, H336	
Γ	CAS: 77-58-7	dibutyltin dilaurate	≥0.1-≤0.25%
	EINECS: 201-039-8	<b>♦</b> Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT	
	Reg.nr.: 01-2119496068-27	RE 1, H372; Skin Corr. 1C, H314; Eye Dam. 1, H318;	
		Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Sens. 1, H317	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

according to 1907/2006/EC, Article 31



Revision: 07.09.2018

Printing date 07.09.2018 Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

(Contd. of page 2)

- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.
- · Information for doctor:

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

water 45 Vol.% ethanol or isopropanol 50 Vol.% ammonia solution (Density= 0.88) 5 Vol.%

- alternatively (non-flammable):

sodium carbonate 5 Vol.% water 95 Vol.%

Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

heet , Article 31

Printing date 07.09.2018

Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

(Contd. of page 3)

Revision: 07.09.2018

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

Store away from foodstuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

6.1 Control parameters		
· Ingre	edients with limit values that require monitoring at the workplace:	
2818	2-81-2 Hexamethylene diisocyanate, oligomers	
EBW	Short-term value: 0.5 mg/m³ exposition evaluation valu TRGS 430 (EBW)	
123-8	86-4 butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
77-58	3-7 dibutyltin dilaurate	
WEL	Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; Sk	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

## · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves (EN 374)

(Contd. on page 5)

according to 1907/2006/EC, Article 31



Revision: 07.09.2018

Printing date 07.09.2018

Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physica	l and c	hemical	properties
--------------------	---------	---------	------------

· 9.1 Information on	basic physical and	chemical properties
----------------------	--------------------	---------------------

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. Not determined.

· pH-value:

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 124°C

· Flash point: 28°C (DIN 53213)

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 370°C (DIN 51794)

Not determined. · Decomposition temperature:

Product is not selfigniting. · Auto-ignition temperature:

Product is not explosive. However, formation of explosive air/ · Explosive properties:

Not determined.

vapour mixtures are possible.

· Explosion limits:

· Evaporation rate

1.2 Vol % Lower: 7.5 Vol % Upper:

10.7 hPa · Vapour pressure at 20°C:

1.03 g/cm³ (DIN 53217) · Density at 20°C:

· Relative density Not determined. Not determined. · Vapour density

· Solubility in / Miscibility with

Not miscible or difficult to mix. water:

(Contd. on page 6)

according to 1907/2006/EC, Article 31

**CR** 

Revision: 07.09.2018

Printing date 07.09.2018

Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

Partition coefficient: n-octanol/water: Not determined.

Viscosity:
Dynamic:
Kinematic at 20°C:
13 s (DIN 53211/4)

Solvent content:
VOC (EC)
45.48 %

Solids content (weight-%):
9.2 Other information
No further relevant information available.

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Possible in traces.

Nitrogen oxides

Hydrogen chloride (HCl)

Hydrogen cyanide (prussic acid)

Carbon monoxide

Nitrogen oxides (NOx)

\*

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

## · LD/LC50 values relevant for classification:

#### 28182-81-2 Hexamethylene diisocyanate, oligomers

Inhalative LC50/4 h 1.5 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

GB

according to 1907/2006/EC, Article 31



Revision: 07.09.2018

Printing date 07.09.2018

Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

(Contd. of page 6)

# SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTI	ON 14:	Trans	port in	format	ion

· 14.1 UN-Number
------------------

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

· ADR UN1263 PAINT RELATED MATERIAL

· IMDG, IATA PAINT RELATED MATERIAL

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 3 (F1) Flammable liquids.

• Label 3

· IMDG, IATA



· Class 3 Flammable liquids.

(Contd. on page 8)

# **Safety data sheet** according to 1907/2006/EC, Article 31



Revision: 07.09.2018

Printing date 07.09.2018

Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

	(Contd. of page		
· Label	3		
· 14.4 Packing group			
· ADR, IMDG, IATA	III		
· 14.5 Environmental hazards:			
· Marine pollutant:	No		
· 14.6 Special precautions for user	Warning: Flammable liquids.		
· Danger code (Kemler):	30		
· EMS Number:	F-E, <u>S-E</u>		
· Stowage Category	A		
14.7 Transport in bulk according to Annex II of			
Marpol and the IBC Code	Not applicable.		
· Transport/Additional information:			
· ADR			
· Transport category	3		
Tunnel restriction code	D/E		
·IMDG			
· Limited quantities (LQ)	5L		
· UN ''Model Regulation'':	UN 1263 PAINT RELATED MATERIAL, 3, III		

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20
- · National regulations:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

May cause drowsiness or dizziness. H336

H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child.

H370 Causes damage to organs.

(Contd. on page 9)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.09.2018

Version number 12

Trade name: 4CR 0408 2K-HS-Härter Low VOC kurz

(Contd. of page 8)

Revision: 07.09.2018

H372Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

# · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity - Category 2

Repr. 1B: Reproductive toxicity - Category 1B

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

 $STOT\ RE\ 1:\ Specific\ target\ organ\ toxicity\ (repeated\ exposure)-Category\ 1$ 

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

\* \* Data compared to the previous version altered.