Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.09.2018

Version number 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: 4CR 2025 Hartspachtel · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Knife filler/ Surfacer \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: 4CR Vertriebsgesellschaft mbH **Oberer Sommerfeldweg 2** D-94469 Deggendorf Tel.: +49 (0) 40 69 60 99 315 Fax: +49 (0) 40 69 60 99 316 E-Mail: Info@4CR.com www.4CR.com • 1.4 Emergency telephone number: +49(0)700 24112112 (CRM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS08 health hazard Repr. 2 H361d Suspected of damaging the unborn child. STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: stvrene

· Hazard statements

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

(Contd. on page 2)

GB

CCR *Revision: 07.09.2018*

Printing date 07.09.2018

Version number 12

Trade name: 4CR 2025 Hartspachtel

	(Contd. of page 1)			
H361d Suspected of damaging the unborn child.				
H372 Causes da	mage to the hearing organs through prolonged or repeated exposure.			
· Precautionary sta	itements			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.			
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P405	Store locked up.			
· 2.3 Other hazards				
· Results of PBT and vPvB assessment				
• <i>PBT:</i> Not applicable.				
· vPvB: Not applicable.				

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

 CAS: 100-42-5
 styrene
 $\geq 10 - \leq 20\%$

 EINECS: 202-851-5
 \Diamond Flam. Liq. 3, H226; \diamondsuit Repr. 2, H361d; STOT RE 1, H372; Asp.
 $\geq 10 - \leq 20\%$

 Reg.nr.: 01-2119457861-32
 \neg Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit.
 $\geq 10 - \leq 20\%$

 Image: Structure of the s

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • *After swallowing: If symptoms persist consult doctor.*

- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.
- Information for doctor:

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2018

Version number 12



Trade name: 4CR 2025 Hartspachtel

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- $\cdot \textit{Further information about storage conditions: Keep container tightly sealed.}$
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm

Long-term value: 430 mg/m³, 100 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

(Contd. on page 4)

(Contd. of page 2)

⁻ GB

Printing date 07.09.2018

Version number 12



Trade name: 4CR 2025 Hartspachtel

(Contd. of page 3)

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Appearance: Form:	Fluid		
Colour:	According to product specification		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/freezing point:	Undetermined.		
Initial boiling point and boiling range:	145.2°C		
· Flash point:	34°C (DIN 53213)		
· Flammability (solid, gas):	Not applicable.		
· Ignition temperature:	480°C (DIN 51794)		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Product is not selfigniting.		
		(Contd. on page 5	

A *Revision: 07.09.2018*

Printing date 07.09.2018

Version number 12

Trade name: 4CR 2025 Hartspachtel

	(Contd. of page
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapour pressure at 20°C:	6 hPa
Density at 20°C:	1.754 g/cm ³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20°C:	9,500 mPas
Kinematic:	Not determined.
Solvent content:	
VOC (EC)	0.55 %
Solids content (weight-%):	85.7 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

100-42-5 styrene

	-	
Oral	LD50	5,000 mg/kg (rat)
		>2,000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31



(Contd. of page 5)

Printing date 07.09.2018

Version number 12

Trade name: 4CR 2025 Hartspachtel

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure
- Causes damage to the hearing organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- *PBT*: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

SECTION 14: Transport information · 14.1 UN-Number · ADR, IMDG, IATA UN3269 · 14.2 UN proper shipping name · ADR UN3269 POLYESTER RESIN KIT · IMDG, IATA UN3269 POLYESTER RESIN KIT · IMDG, IATA POLYESTER RESIN KIT · IA.3 Transport hazard class(es) · · ADR ✓ · Class 3 (F3) Flammable liquids.



Printing date 07.09.2018

Version number 12

Trade name: 4CR 2025 Hartspachtel

	(Contd. of pa
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDĞ, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	-
EMS Number:	F-E,S-D
Stowage Category	A
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Transport category	3
Tunnel restriction code	Ε
- IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

Class | Share in %

NK 10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases


H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 8)

[·] Directive 2012/18/EU

GB



Version number 12



Trade name: 4CR 2025 Hartspachtel

(Contd. of page 7)
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to the hearing organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
· Classification according to Regulation (EC) No 1272/2008
The classification of the mixture is generally based on the calculation method using substance data according
to Regulation (EC) No 1272/2008.
· Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1
Asp. 10x, 1: Aspiration nazara – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
\cdot * Data compared to the previous version altered.
GB