according to 1907/2006/EC, Article 31



Revision: 25.03.2015

Printing date 25.03.2015

Version number 8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 4CR 2500 Spritzfüller
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

4CR Vertriebsgesellschaft mbH

Oberer Sommerfeldweg 2

94469 Deggendorf

Tel.: + 49 (0) 48 41-6650-15 Fax: +49(0)4841-6650-16

e-Mail: order@4cr.de

· 1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20-48/20-63: Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child.



Xi; Irritant

R36/38: Irritating to eyes and skin.

Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Version number 8 Revision: 25.03.2015

Trade name: 4CR 2500 Spritzfüller

(Contd. of page 1)

· 2.2 Label elements

Printing date 25.03.2015

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

styrene

- · Hazard statements
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 100-42-5	styrene	12.5-<25%
EINECS: 202-851-5	<b>X</b> Xn R20-48/20-63; <b>X</b> Xi R36/38	
Reg.nr.: 01-2119457861-32		
	<ul> <li>Flam. Liq. 3, H226;</li> <li>Repr. 2, H361d; STOT RE 1, H372;</li> <li>Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319</li> </ul>	
CAS: 141-78-6	ethyl acetate	3-<10%
EINECS: 205-500-4	<b>★</b> Xi R36; <b>→</b> F R11	
Reg.nr.: 01-2119475103-46	<del>R6</del> 6-67	
	🚸 Flam. Liq. 2, H225; <page-header> Eye Irrit. 2, H319; STOT SE 3, H336</page-header>	
	(0	Contd. on page 3

age 3)

according to 1907/2006/EC, Article 31 Version number 8

Printing date 25.03.2015

Trade name: 4CR 2500 Spritzfüller

(Contd. of page 2)

Revision: 25.03.2015

· Additional information: For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

**SECTION 5: Firefighting measures** 

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Revision: 25.03.2015

Printing date 25.03.2015 Version number 8

Trade name: 4CR 2500 Spritzfüller

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with	limit values tha	t require	monitoring	at the	workplace:

100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date 25.03.2015

 $Version\ number\ 8$ 

Trade name: 4CR 2500 Spritzfüller

(Contd. of page 4)

Revision: 25.03.2015

 $\cdot$  Eye protection:



Tightly sealed goggles

9.1 Information on basic physical	and chemical properties
General Information	
Appearance:	
Form:	Fluid
Colour: Odour:	According to product specification Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C
Flash point:	31 °C (DIN 53213)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	480 °C (DIN 51794)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapour pressure at 20 °C:	6 hPa
Density at 20 °C:	$1.504 \ g/cm^3 (DIN 53217)$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	N
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wo	nter): Not determined.
Viscosity:	10000 P
Dynamic at 20 °C:	10000 mPas
Kinematic:	Not determined.
Solvent content: VOC (EC)	5.10 %
Solids content (weight-%):	72.0 %
9.2 Other information	No further relevant information available.

according to 1907/2006/EC, Article 31

V ---- - - - 0

Version number 8

Trade name: 4CR 2500 Spritzfüller

(Contd. of page 5)

Revision: 25.03.2015

### SECTION 10: Stability and reactivity

· 10.1 Reactivity

Printing date 25.03.2015

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:			
100-42-5 styrene			
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rat)	
Inhalative	LC50/4 h (Dämpfe)	11.8 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Renr 2

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

GB



Revision: 25.03.2015

Printing date 25.03.2015 Version number 8

Trade name: 4CR 2500 Spritzfüller

(Contd. of page 6)

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	ion	
· 14.1 UN-Number · ADR, IMDG, IATA	UN3269	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	3269 POLYESTER RESIN KIT POLYESTER RESIN KIT	
· 14.3 Transport hazard class(es)		
$\cdot ADR$		
3		
· Class	3 (F3) Flammable liquids.	
· Label · IMDG, IATA	3	
· Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Flammable liquids.	
· Danger code (Kemler): · EMS Number:	- F-E,S-D	
· 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	e <b>x II of</b> Not applicable.	
· Transport/Additional information:		
$\cdot ADR$		
· Transport category · Tunnel restriction code	3 E	

(Contd. on page 8)

Version number 8 Revision: 25.03.2015

Trade name: 4CR 2500 Spritzfüller

Printing date 25.03.2015

(Contd. of page 7) · IMDG · Limited quantities (LQ) 5L· UN ''Model Regulation'': UN3269, POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

(Contd. on page 9)

Version number 8



Revision: 25.03.2015

Trade name: 4CR 2500 Spritzfüller

Printing date 25.03.2015

(Contd. of page 8)

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

\* Data compared to the previous version altered.