

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 4CR 5250 Unterbodenschutzwachs Spray
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Surface protection
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
4CR Vertriebsgesellschaft mbH  
Oberer Sommerfeldweg 2  
D-94469 Deggendorf  
Tel.: +49 (0) 40 69 60 99 315  
Fax: +49 (0) 40 69 60 99 316  
E-Mail: [Info@4CR.com](mailto:Info@4CR.com)  
[www.4CR.com](http://www.4CR.com)
- **1.4 Emergency telephone number:** +49(0)700 24112112 (CRM)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1            H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*



GHS07

|                   |      |  |
|-------------------|------|--|
| Skin Irrit. 2     | H315 | Causes skin irritation.                            |
| STOT SE 3         | H336 | May cause drowsiness or dizziness.                 |
| Asp. Tox. 1       | H304 | May be fatal if swallowed and enters airways.      |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**  
*Hydrocarbons, C9, aromatics*  
*Naphtha (petroleum), hydrotreated light*  
*Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics*  
*Naphtha (petroleum), hydrodesulfurized heavy*
- **Hazard statements**  
*H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.*  
*H315 Causes skin irritation.*  
*H336 May cause drowsiness or dizziness.*  
*H412 Harmful to aquatic life with long lasting effects.*

(Contd. on page 2)

**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 1)

· **Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P405 Store locked up.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.  
 · **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

|   |  |            |
|---|--|------------|
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Reg.nr.: 01-21194869440-21   | propane<br>⚠ Flam. Gas 1, H220; Press. Gas C, H280   | 10-25%     |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Reg.nr.: 01-2119485395-27    | isobutane<br>⚠ Flam. Gas 1, H220; Press. Gas C, H280   | 10-25%     |
| CAS: 64742-49-0<br>EINECS: 265-151-9<br>Reg.nr.: 01-2119475514-35 | Naphtha (petroleum), hydrotreated light<br>⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336          | 2.5-<10%   |
| EC number: 927-510-4<br>Reg.nr.: 01-2119475515-33                 | Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics<br>⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | 2.5-<10%   |
| EC number: 918-668-5<br>Reg.nr.: 01-2119455851-35                 | Hydrocarbons, C9, aromatics<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336                                      | 2.5-<10%   |
| CAS: 64742-82-1<br>EINECS: 265-185-4                              | Naphtha (petroleum), hydrodesulfurized heavy<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336                          | 2.5-<10%   |
| CAS: 67-56-1<br>EINECS: 200-659-6                                 | methanol<br>⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370  | ≥0.1-<2.5% |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.  
 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.  
 · **After eye contact:** Rinse opened eye for several minutes under running water.  
 · **After swallowing:** Seek immediate medical advice.

(Contd. on page 3)

**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.
- **Information for doctor:**

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Do not seal receptacle gas tight.  
Keep container tightly sealed.

(Contd. on page 4)

**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 3)

- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- **Storage class: 2 B**
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**67-56-1 methanol**

|     |   |
|-----|---|
| WEL | Short-term value: 333 mg/m <sup>3</sup> , 250 ppm |
|     | Long-term value: 266 mg/m <sup>3</sup> , 200 ppm  |
| Sk  |   |

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.

- **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

- **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Breakthrough time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

|                    |                                    |
|--------------------|------------------------------------|
| Form:              | Aerosol                            |
| Colour:            | According to product specification |
| · Odour:           | Characteristic                     |
| · Odour threshold: | Not determined.                    |

· pH-value: Not determined.

· Change in condition

|  |               |
|--|---------------|
| Melting point/freezing point:            | Undetermined. |
| Initial boiling point and boiling range: | -44°C         |

· Flash point: &lt;0°C (DIN 53213)

· Flammability (solid, gas): Not applicable.

· Ignition temperature: &gt;200°C (DIN 51794)

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

|        |            |
|--------|------------|
| Lower: | 1.7 Vol %  |
| Upper: | 10.9 Vol % |

· Vapour pressure at 20°C: 8,300 hPa

· Density at 20°C: 0.746 g/cm<sup>3</sup> (DIN 53217)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

|            |                 |
|------------|-----------------|
| Dynamic:   | Not determined. |
| Kinematic: | Not determined. |

· Solvent content:

VOC (EC) 67.70 %

Solids content (weight-%): 32.3 %

· 9.2 Other information: No further relevant information available.

GB

(Contd. on page 6)

**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 5)

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**64742-49-0 Naphtha (petroleum), hydrotreated light**

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | >2,000 mg/kg (rabbit) |
| Dermal     | LD50     | >2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >190 mg/l (rat)       |

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 5,840 mg/kg (rat) |
| Dermal     | LD50     | 2,920 mg/kg (rat) |
| Inhalative | LC50/4 h | 23.3 mg/l (rat)   |

**Hydrocarbons, C9, aromatics**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | >2,000 mg/kg (rat)    |
| Dermal | LD50 | >2,000 mg/kg (rabbit) |

**67-56-1 methanol**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | 5,628 mg/kg (rat)     |
| Dermal | LD50 | 15,800 mg/kg (rabbit) |

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

(Contd. on page 7)

**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 6)

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

**64742-49-0 Naphtha (petroleum), hydrotreated light**

EC50 >1,000 mg/kg (bacteria)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

##### · Ecotoxicological effects:

· **Remark:** Harmful to fish

##### · Additional ecological information:

##### · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

##### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### · European waste catalogue

16 05 04\* | gases in pressure containers (including halons) containing hazardous substances

15 01 10\* | packaging containing residues of or contaminated by hazardous substances

##### · Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

#### · 14.1 UN-Number

· **ADR, IMDG, IATA**

UN1950

#### · 14.2 UN proper shipping name

· **ADR**

UN1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

#### · 14.3 Transport hazard class(es)

· **ADR**




· **Class**

2 5F Gases.

(Contd. on page 8)

**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 7)

|  |   |
|--|---|
| · <b>Label</b>   | 2.1   |
| -----  |   |
| · <b>IMDG, IATA</b>  |   |
|     |   |
| · <b>Class</b>   | 2.1   |
| · <b>Label</b>   | 2.1   |
| -----  |   |
| · <b>14.4 Packing group</b>  |   |
| · <b>ADR, IMDG, IATA</b>   | Void  |
| -----  |   |
| · <b>14.5 Environmental hazards:</b>   | Product contains environmentally hazardous substances:<br>Naphtha (petroleum)   |
| · <b>Marine pollutant:</b>   | No  |
| -----  |   |
| · <b>14.6 Special precautions for user</b>   | Warning: Gases.   |
| · <b>Danger code (Kemler):</b>   | -   |
| · <b>EMS Number:</b>   | F-D,S-U   |
| · <b>Stowage Code</b>  | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre:<br>Category A. For AEROSOLS with a capacity above 1 litre:<br>Category B. For WASTE AEROSOLS: Category C, Clear<br>of living quarters.   |
| · <b>Segregation Code</b>  | SG69 For AEROSOLS with a maximum capacity of 1 litre:<br>Segregation as for class 9. Stow "separated from" class 1<br>except for division 1.4. For AEROSOLS with a capacity<br>above 1 litre: Segregation as for the appropriate<br>subdivision of class 2. For WASTE AEROSOLS:<br>Segregation as for the appropriate subdivision of class 2. |
| -----  |   |
| · <b>14.7 Transport in bulk according to Annex II of<br/>Marpol and the IBC Code</b> | Not applicable.   |
| -----  |   |
| · <b>Transport/Additional information:</b>   |   |
| -----  |   |
| · <b>ADR</b>   |   |
| · <b>Transport category</b>  | 2   |
| · <b>Tunnel restriction code</b>   | D   |
| -----  |   |
| · <b>IMDG</b>  |   |
| · <b>Limited quantities (LQ)</b>   | 1L  |
| -----  |   |
| · <b>UN "Model Regulation":</b>  | UN 1950 AEROSOLS, 2.1   |

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I methanol**
- **Seveso category P3a FLAMMABLE AEROSOLS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t**
- **Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t**
- **REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3**

(Contd. on page 9)



**Trade name: 4CR 5250 Unterbodenschutzwachs Spray**

(Contd. of page 8)

· **National regulations:**

| Class | Share in % |
|-------|------------|
| I     | ≥0.1-<2.5  |
| NK    | 10-25      |

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H370 Causes damage to organs.
- H411 Toxic to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas C: Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**