Safety data sheet

according to 1907/2006/EC, Article 31



GB

Printing date 07.09.2018

Version number 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: 4CR 7200 Klarlack HS 2:1 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Paint \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: 4CR Vertriebsgesellschaft mbH **Oberer Sommerfeldweg 2** D-94469 Deggendorf Tel.: +49 (0) 40 69 60 99 315 Fax: +49 (0) 40 69 60 99 316 E-Mail: Info@4CR.com www.4CR.com • 1.4 Emergency telephone number: +49(0)700 24112112 (CRM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Warning · Hazard-determining components of labelling: butyl acetate Hydrocarbons, C9, aromatics Reaction mass of pentamethyl-piperidyl sebacate 2,3-epoxypropyl neodecanoate · Hazard statements H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. (Contd. on page 2)

Revision: 07.09.2018

Printing date 07.09.2018

Version number 10

Trade name: 4CR 7200 Klarlack HS 2:1

	(Contd. of page 1)
· Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+1	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional info	prmation:
EUH066 Repe	ated exposure may cause skin dryness or cracking.
\cdot 2.3 Other haza	urds
Degulta of DD	Ford white according to the

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

*

Г

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

 $\cdot \textit{Description: Mixture of substances listed below with nonhazardous additions.}$

· Dangerous components:


CAS: 123-86-4	butyl acetate	25-50%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
EC number: 918-668-5	Hydrocarbons, C9, aromatics	2.5-<10%
Reg.nr.: 01-2119455851-35	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	
CAS: 112-07-2	2-butoxyethyl acetate	2.5-<10%
EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	() Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 1330-20-7	xylene	≥0.1-<5%
EINECS: 215-535-7	🚸 Flam. Liq. 3, H226; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304;	
Reg.nr.: 01-2119488216-32	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 100-41-4	ethylbenzene	≥0.1-<2.5%
EINECS: 202-849-4	🚸 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304;	
Reg.nr.: 01-2119489370-35	Acute Tox. 4, H332; Škin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
EC number: 915-687-0	Reaction mass of pentamethyl-piperidyl sebacate	≥ 0.25-<1%
Reg.nr.: 01-2119491304-40	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🚸 Skin Sens. 1A, H317	
CAS: 26761-45-5	2,3-epoxypropyl neodecanoate	≥0.25-<1%
EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	♦ Muta. 2, H341; ♦ Aquatic Chronic 2, H411; ♦ Skin Sens. 1, H317	

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31



Version number 10



Trade name: 4CR 7200 Klarlack HS 2:1

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.
- Information for doctor:

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

• Storage class: 3

(Contd. on page 4)

_____(

Printing date 07.09.2018

Version number 10



Trade name: 4CR 7200 Klarlack HS 2:1

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Co	· 8.1 Control parameters		
· Ingrea	ients with limit values that require monitoring at the workplace:		
123-80	5-4 butyl acetate		
WEL .	Short-term value: 966 mg/m³, 200 ppm		
	Long-term value: 724 mg/m³, 150 ppm		
112-07	7-2 2-butoxyethyl acetate		
WEL	Short-term value: 332 mg/m³, 50 ppm		
	Long-term value: 133 mg/m³, 20 ppm		
	Sk		
1330-2	1330-20-7 xylene		
WEL	Short-term value: 441 mg/m³, 100 ppm		
	Long-term value: 220 mg/m³, 50 ppm		
	Sk; BMGV		
100-41	-4 ethylbenzene		
WEL 1	Short-term value: 552 mg/m³, 125 ppm		
	Long-term value: 441 mg/m³, 100 ppm		
	Sk		
· Ingredients with biological limit values:			
1330-2	20-7 xylene		
BMGV	650 mmol/mol creatinine		
	Medium: urine		
	Sampling time: post shift		
	Parameter: methyl hippuric acid		
A 11.4	and information. The lists valid during the making were used as having		

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

(Contd. of page 3)

⁻ GB



Printing date 07.09.2018

Version number 10

Trade name: 4CR 7200 Klarlack HS 2:1

(Contd. of page 4)

GB

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:




2

Tightly sealed goggles

9.1 Information on basic physical and of	chemical properties
General Information Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
Flash point:	36°C (DIN 53213)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	280°C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20°C:	10.7 hPa
Density at 20°C:	0.994 g/cm ³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20°C:	90 s (DIN 53211/4)
Solvent content:	
VOC (EC)	50.81 %
Solids content (weight-%):	49.2 %

Safety data sheet

according to 1907/2006/EC, Article 31



Version number 10



(Contd. of page 5)

Trade name: 4CR 7200 Klarlack HS 2:1

• 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C9, aromatics

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Remark: Harmful to fish
- $\cdot \textit{Additional ecological information:}$
- · General notes:
- Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Harmful to aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.


(Contd. on page 7)

GB

2

2

Safety data sheet according to 1907/2006/EC, Article 31



Version number 10



Trade name: 4CR 7200 Klarlack HS 2:1

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN1263 PAINT PAINT	
· 14.3 Transport hazard class(es) · ADR		
· Class · Label	3 (F1) Flammable liquids. 3	
· Class	3 Flammable liquids.	
·Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards: Marine pollutant:	No	
-	Waming, Elammahla liquida	
14.6 Special precautions for user	Warning: Flammable liquids.	
• 14.6 Special precautions for user • Danger code (Kemler):	30	
• 14.6 Special precautions for user		

(Contd. of page 6)

CCR *Revision: 07.09.2018*

Printing date 07.09.2018

Version number 10

Trade name: 4CR 7200 Klarlack HS 2:1

		(Contd. of page 7)
· Transport/Additional information:		
$\cdot ADR$		
· Transport category	3	
• Tunnel restriction code	D/E	
· Remarks:	<i>≤</i> 450 <i>l</i> : -	
· IMDG		
\cdot Limited quantities (LQ)	5L	
· Remarks:	<i>≤ 30 l: -</i>	
· UN ''Model Regulation'':	UN 1263 PAINT, 3, III	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. · Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 9)

GB

A *Revision: 07.09.2018*

(Contd. of page 8)

Printing date 07.09.2018

Version number 10

Trade name: 4CR 7200 Klarlack HS 2:1

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Muta. 2: Germ cell mutagenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \cdot * Data compared to the previous version altered.