according to 1907/2006/EC, Article 31

Revision: 07.06.2019

Printing date 07.06.2019

Version number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 4CR 7265 Premium 2K UHS Klarlack
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Clear coating material, Varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

4CR Vertriebsgesellschaft mbH

Oberer Sommerfeldweg 2

D-94469 Deggendorf

Tel.: +49 (0) 40 69 60 99 315 Fax: +49 (0) 40 69 60 99 316

E-Mail: Info@4CR.com

www.4CR.com

• 1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

# SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

- · Signal word Warning
- · Hazard-determining components of labelling:

n-Butyl acetate

2-ethoxy-1-methylethyl acetate

2-Methoxy-1-methylethyl acetate

Reaction mass of pentamethyl-piperidyl sebacate

· Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Revision: 07.06.2019

Printing date 07.06.2019

Version number 1

#### Trade name: 4CR 7265 Premium 2K UHS Klarlack

(Contd. of page 1)

· i recaulimary sialements		Prec	autionary	statements
----------------------------	--	------	-----------	------------

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 123-86-4	n-Butyl acetate	10-25%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🏇 Flam. Liq. 3, H226; 🕚 STOT SE 3, H336	
CAS: 763-69-9 EINECS: 212-112-9 Reg.nr.: 01-2119463267-34	ethyl 3-ethoxypropionate  Flam. Liq. 3, H226	2.5-<10%
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-ethoxy-1-methylethyl acetate  Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate  Flam. Liq. 3, H226;  STOT SE 3, H336	2.5-<10%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidyl sebacate  Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.25-<19
CAS: 868-77-9 EINECS: 212-782-2 Reg.nr.: 01-2119490169-29	2-hydroxyethyl methacrylate  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<1%
CAS: 97-86-9 EINECS: 202-613-0 Reg.nr.: 01-2119488331-38	isobutyl methacrylate  Flam. Liq. 3, H226; Aquatic Acute 1, H400; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.25
CAS: 7575-23-7 EINECS: 231-472-8 Reg.nr.: 01-2119486981-23	Pentaerythritol tetrakis(3-mercaptopropionate)  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Tox. 4, H302; Skin Sens. 1A, H317	≥0.025-<0.1

according to 1907/2006/EC, Article 31

Revision: 07.06.2019

Printing date 07.06.2019

Version number 1

Trade name: 4CR 7265 Premium 2K UHS Klarlack

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

· Information for doctor:

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

4<sub>CR</sub>

Revision: 07.06.2019

Printing date 07.06.2019

Version number 1

Trade name: 4CR 7265 Premium 2K UHS Klarlack

(Contd. of page 3)

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

### 123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

## 108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

- GB

# **Safety data sheet** according to 1907/2006/EC, Article 31



Revision: 07.06.2019

Printing date 07.06.2019 Version number 1

Trade name: 4CR 7265 Premium 2K UHS Klarlack

(Contd. of page 4)

# SECTION 9: Physical and chemical properties

9.	1	Information	on	basic	physical	and	chemical	properties
-•	_	110,0111100000	011	Custe	picystett	~~~~	circinite ar	properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

*Melting point/freezing point:* Undetermined. Initial boiling point and boiling range: 124 °C

27 °C (DIN EN ISO 1523:2002) · Flash point:

· Flammability (solid, gas): Not applicable.

370 °C (DIN 51794) · Ignition temperature:

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

Product is not explosive. However, formation of explosive air/ · Explosive properties:

vapour mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol % 7.5 Vol % Upper:

· Vapour pressure at 20 °C: 10.7 hPa

· Density at 20 °C: 1.023 g/cm<sup>3</sup> (DIN EN ISO 2811-1)

Not determined. · Relative density · Vapour density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

Not miscible or difficult to mix. water:

Not determined. · Partition coefficient: n-octanol/water:

· Viscosity:

Dynamic: Not determined. Kinematic at 20 °C: 32-35 s (DIN 53211/4)

· Solvent content:

VOC (EC) 38.86 %

61.1 % Solids content (weight-%):

· 9.2 Other information No further relevant information available.

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

**CR** 

Revision: 07.06.2019

Printing date 07.06.2019

Version number 1

Trade name: 4CR 7265 Premium 2K UHS Klarlack

(Contd. of page 5)

· 10.6 Hazardous decomposition products: Carbon monoxide

# **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

 $Do \ not \ allow \ product \ to \ reach \ ground \ water, \ water \ course \ or \ sewage \ system.$ 

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

(Contd. on page 7)

# Safety data sheet according to 1907/2006/EC, Article 31



Printing date 07.06.2019 Version number 1 Revision: 07.06.2019

Trade name: 4CR 7265 Premium 2K UHS Klarlack

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR IMDG, IATA	UN1263 PAINT PAINT	
14.3 Transport hazard class(es)		
ADR		
Class	2 (E1) El gum abla liquida	
· Class · Label	3 (F1) Flammable liquids. 3	
IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	III	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Warning: Flammable liquids.	
Danger code (Kemler):	30	
EMS Number: Stowage Category	F-E, <u>S-E</u> A	
14.7 Transport in bulk according to Anne Marpol and the IBC Code	ex II of Not applicable.	
Transport/Additional information:		
ADR Transport category Tunnel restriction code	3 D/E	
IMDG Limited quantities (LQ)	5L	

according to 1907/2006/EC, Article 31

4<sub>CR</sub>

Revision: 07.06.2019

Printing date 07.06.2019

Version number 1

Trade name: 4CR 7265 Premium 2K UHS Klarlack

(Contd. of page 7)

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

## · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* \* Data compared to the previous version altered.

GB ·