according to 1907/2006/EC, Article 31



Revision: 07.09.2018

Printing date 07.09.2018

Version number 6

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 4CR 7422 Kontrollspray
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

4CR Vertriebsgesellschaft mbH

Oberer Sommerfeldweg 2

D-94469 Deggendorf

*Tel.*: +49 (0) 40 69 60 99 315 *Fax*: +49 (0) 40 69 60 99 316

E-Mail: Info@4CR.com

www.4CR.com

• 1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

acetone

butyl acetate

methyl ethyl ketone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

(Contd. on page 2)

according to 1907/2006/EC, Article 31



Revision: 07.09.2018

*Printing date 07.09.2018* 

Version number 6

Trade name: 4CR 7422 Kontrollspray

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

#### SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:  CAS: 67-64-1                            | acetone  | 25-50%             |
|--|--|--------------------|
| EINECS: 200-662-2<br>Reg.nr.: 01-2119471330-49                   | ♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3, H336  | 23-3070            |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Reg.nr.: 01-2119485493-29  | butyl acetate  Flam. Liq. 3, H226; STOT SE 3, H336   | ≥10-≤20%           |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Reg.nr.: 01-21194869440-21  | propane  Flam. Gas 1, H220; Press. Gas C, H280   | 10-25%             |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Reg.nr.: 01-2119474691-31  | butane Flam. Gas 1, H220; Press. Gas C, H280   | 10-25%             |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Reg.nr.: 01-2119475791-29  | 2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226  | ≥0.1-<2.5%         |
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Reg.nr.: 01-2119488216-32 | xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | <i>≥</i> 0.1-<2.5% |
| CAS: 1333-86-4<br>EINECS: 215-609-9<br>Reg.nr.: 01-2119384822-32 | Carbon black substance with a Community workplace exposure limit   | ≥0.1-<2.5%         |
| CAS: 78-93-3<br>EINECS: 201-159-0<br>Reg.nr.: 01-2119457290-43   | methyl ethyl ketone  Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336   | ≥0.1-<2.5%         |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

2)

(Contd. on page 3)

according to 1907/2006/EC, Article 31

4cR

Revision: 07.09.2018

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7422 Kontrollspray

(Contd. of page 2)

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

· Information for doctor:

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

- GB

ſ

L

Version number 6

Printing date 07.09.2018

(Contd. of page 3)

Revision: 07.09.2018

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Trade name: 4CR 7422 Kontrollspray

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2 B
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

| SECTION 8: | Exposure | controls/ | /personal | protection |
|------------|----------|-----------|-----------|------------|
|------------|----------|-----------|-----------|------------|

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

1330-20-7 xylene

| dients with limit values that require monitoring at the workplace:  |
|---|
| -1 acetone  |
| Short-term value: 3620 mg/m³, 1500 ppm<br>Long-term value: 1210 mg/m³, 500 ppm  |
| 6-4 butyl acetate   |
| Short-term value: 966 mg/m³, 200 ppm<br>Long-term value: 724 mg/m³, 150 ppm   |
| 7-8 butane  |
| Short-term value: 1810 mg/m³, 750 ppm<br>Long-term value: 1450 mg/m³, 600 ppm<br>Carc (if more than 0.1% of buta-1.3-diene) |
| 5-6 2-methoxy-1-methylethyl acetate   |
| Short-term value: 548 mg/m³, 100 ppm<br>Long-term value: 274 mg/m³, 50 ppm<br>Sk  |
| 20-7 xylene   |
| Short-term value: 441 mg/m³, 100 ppm<br>Long-term value: 220 mg/m³, 50 ppm<br>Sk; BMGV                                      |
| 86-4 Carbon black   |
| Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³  |
| -3 methyl ethyl ketone  |
| Short-term value: 899 mg/m³, 300 ppm<br>Long-term value: 600 mg/m³, 200 ppm<br>Sk, BMGV                                     |
|   |

(Contd. on page 5)

according to 1907/2006/EC, Article 31

**CR** 

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7422 Kontrollspray

(Contd. of page 4)

Revision: 07.09.2018

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

#### 78-93-3 methyl ethyl ketone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

· Odour: Characteristic

(Contd. on page 6)



Revision: 07.09.2018

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7422 Kontrollspray

|   | (Contd. of page :   |
|---|---|
| · Odour threshold:  | Not determined.   |
| · pH-value:   | Not determined.   |
| · Change in condition<br>Melting point/freezing point:<br>Initial boiling point and boiling range | Undetermined.<br>: -44°C  |
| · Flash point:  | <0°C (DIN 53213)  |
| · Flammability (solid, gas):  | Not applicable.   |
| · Ignition temperature:   | 365°C (DIN 51794)   |
| · Decomposition temperature:  | Not determined.   |
| · Auto-ignition temperature:  | Product is not selfigniting.  |
| · Explosive properties:   | Product is not explosive. However, formation of explosive air vapour mixtures are possible. |
| · Explosion limits:<br>Lower:<br>Upper:   | 1.2 Vol %<br>13 Vol %   |
| · Vapour pressure at 20°C:  | 8,300 hPa   |
| · Density at 20°C:<br>· Relative density<br>· Vapour density<br>· Evaporation rate                | 0.781 g/cm³ (DIN 53217)<br>Not determined.<br>Not determined.<br>Not applicable.            |
| · Solubility in / Miscibility with water:   | Not miscible or difficult to mix.   |
| · Partition coefficient: n-octanol/water:   | Not determined.   |
| · Viscosity: Dynamic: Kinematic:  | Not determined.<br>Not determined.  |
| · Solvent content:<br>VOC (EC)  | 89.64 %   |
| Solids content (weight-%): • 9.2 Other information  | 10.4 %<br>No further relevant information available.  |

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

according to 1907/2006/EC, Article 31

**CR** 

Revision: 07.09.2018

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7422 Kontrollspray

(Contd. of page 6)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.} \\$
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European waste catalogue |   |
|----------------------------|---|
| 08 01 11*                  | waste paint and varnish containing organic solvents or other hazardous substances |
| 14 06 03*                  | other solvents and solvent mixtures   |
| 15 01 04                   | metallic packaging  |

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

#### SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG AEROSOLS

(Contd. on page 8)

 $\cdot$  *IMDG* 

· Limited quantities (LQ)

· UN "Model Regulation":

## Safety data sheet

according to 1907/2006/EC, Article 31



Revision: 07.09.2018

Printing date 07.09.2018

Trade name: 4CR 7422 Kontrollspray

Version number 6

(Contd. of page 7)  $\cdot$  IATA AEROSOLS, flammable · 14.3 Transport hazard class(es)  $\cdot ADR$ 2 5F Gases. · Class 2.1 · Label · IMDG, IATA · Class 2.1 · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D,S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: · Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: *Segregation as for the appropriate subdivision of class 2.* · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: 2 · Transport category · Tunnel restriction code D

1L

UN 1950 AEROSOLS, 2.1

-GR

Revision: 07.09.2018

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7422 Kontrollspray

(Contd. of page 8)

#### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · National regulations:

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 10)

Printing date 07.09.2018

Version number 6

(Contd. of page 9)

Revision: 07.09.2018

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

\* Data compared to the previous version altered.

Trade name: 4CR 7422 Kontrollspray