Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 07.09.2018

Version number 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: 4CR 7442 WBS Prefill Spray · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Paint · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: 4CR Vertriebsgesellschaft mbH **Oberer Sommerfeldweg 2** D-94469 Deggendorf Tel.: +49 (0) 40 69 60 99 315 Fax: +49 (0) 40 69 60 99 316 E-Mail: Info@4CR.com www.4CR.com • 1.4 Emergency telephone number: +49(0)700 24112112 (CRM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. GHS07 Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: acetone butan-1-ol · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Precautionary statements If medical advice is needed, have product container or label at hand. P101 P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Revision: 07.09.2018

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7442 WBS Prefill Spray

| | (Contd. of page 1) |
|---------------------|--|
| P251 | Do not pierce or burn, even after use. |
| P305+P351+P33 | 8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if |
| | present and easy to do. Continue rinsing. |
| P405 | Store locked up. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international |
| | regulations. |
| · Additional inform | ation: |
| EUH066 Repeated | l exposure may cause skin dryness or cracking. |
| · 2.3 Other hazards | |
| · Results of PBT ar | nd vPvB assessment |

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| EINECS: 204-065-8 Flam. Gas 1, H220; Press. Gas L, H280 Reg.nr.: 01-2119472128-37 acetone CAS: 67-64-1 acetone EINECS: 200-662-2 Flam. Liq. 2, H225; Deg Irrit. 2, H319; STOT SE 3, H336 Reg.nr.: 01-2119471330-49 Flam. Liq. 2, H225; Deg Irrit. 2, H319; STOT SE 3, H336 | 50-100% 25-50% ≥0.1-<5% |
|---|-------------------------------|
| EINECS: 200-662-2 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 Reg.nr.: 01-2119471330-49 xylene CAS: 1330-20-7 xylene EINECS: 215-535-7 Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Reg.nr.: 01-2119488216-32 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; | |
| EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; | >01-<5% |
| <i>Eye Irru. 2, 1519; SIOI SE 5, 1555</i> | -0.1 (570 |
| CAS: 71-36-3 butan-1-ol ≥ EINECS: 200-751-6 Image: Flam. Liq. 3, H226; Image: Eye Dam. 1, H318; Image: Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 ≥ | ≥2.5-≤3% |
| CAS: 67-56-1 methanol ≥0 EINECS: 200-659-6 Image: Flam. Liq. 2, H225; Image: Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Image: STOT SE 1, H370 ≥0 | 20.1-<2.5% |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.09.2018

Version number 6



Trade name: 4CR 7442 WBS Prefill Spray

• Information for doctor:

(Contd. of page 2)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. · Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurised containers. • Information about storage in one common storage facility: Store away from foodstuffs. • Further information about storage conditions: Do not seal receptacle gas tight. Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. · Storage class: 2 B

(Contd. on page 4)

GB

Printing date 07.09.2018

Version number 6



(Contd. of page 3)

Trade name: 4CR 7442 WBS Prefill Spray

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

| · 8.1 Cont | trol parameters |
|------------|---|
| · Ingredie | nts with limit values that require monitoring at the workplace: |
| 115-10-6 | 6 dimethyl ether |
| WEL Sh | ort-term value: 958 mg/m³, 500 ppm |
| Lo | ng-term value: 766 mg/m³, 400 ppm |
| 67-64-1 | acetone |
| WEL Sh | ort-term value: 3620 mg/m³, 1500 ppm |
| Lo | ong-term value: 1210 mg/m³, 500 ppm |
| 1330-20 | -7 xylene |
| | ort-term value: 441 mg/m³, 100 ppm |
| | ng-term value: 220 mg/m³, 50 ppm |
| Sk | ; BMGV |
| 71-36-3 | butan-1-ol |
| WEL Sh | ort-term value: 154 mg/m³, 50 ppm |
| Sk | |
| 67-56-1 | methanol |
| WEL Sh | ort-term value: 333 mg/m³, 250 ppm |
| Lo | ng-term value: 266 mg/m³, 200 ppm |
| Sk | |
| Ingredie | nts with biological limit values: |
| 1330-20- | -7 xylene |
| BMGV | 650 mmol/mol creatinine |
| İ | Medium: urine |
| | Sampling time: post shift |
| 1 | Parameter: methyl hippuric acid |
| | Sampling time: post shift |

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:



Protective gloves (EN 374)

(Contd. on page 5)

GB

A *Revision: 07.09.2018*

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7442 WBS Prefill Spray

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:




Tightly sealed goggles

| 9.1 Information on basic physical an | nd chemical properties |
|--------------------------------------|---|
| General Information | |
| Appearance: | |
| Form: | Aerosol |
| Colour: | According to product specification |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling ra | unge: -24°C |
| Flash point: | <0°C (DIN 53213) |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 235°C (DIN 51794) |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 2.6 Vol % |
| Upper: | 18.6 Vol % |
| • Vapour pressure at 20°C: | 5,200 hPa |
| Density at 20°C: | 0.71 g/cm ³ (DIN 53217) |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| • Evaporation rate | Not applicable. |

Safety data sheet

according to 1907/2006/EC, Article 31



Version number 6



Trade name: 4CR 7442 WBS Prefill Spray

| | | (Contd. of page 2 |
|---|--|-------------------|
| Solubility in / Miscibility with | | |
| water: | Not miscible or difficult to mix. | |
| · Partition coefficient: n-octanol/water: | Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Water: | 0.3 % | |
| VOC (EC) | 99.49 % | |
| Solids content (weight-%): | 0.3 % | |
| • 9.2 Other information | No further relevant information available. | |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

 \cdot Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-56-1 methanol

Oral LD50 5,628 mg/kg (rat)

Dermal LD50 15,800 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- \cdot Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 7)



(Contd. of page 6)

Printing date 07.09.2018

Version number 6

Trade name: 4CR 7442 WBS Prefill Spray

· 12.3 Bioaccumulative potential No further relevant information available.

- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| ·European | waste | catalogue |
|-----------|-------|-----------|
|-----------|-------|-----------|

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

14 06 03* other solvents and solvent mixtures

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

| · 14.1 UN-Number | | |
|-----------------------------------|---------------------|--|
| · ADR, IMDG, IATA | UN1950 | |
| · 14.2 UN proper shipping name | | |
| · ADR | UN1950 AEROSOLS | |
| ·IMDG | AEROSOLS | |
| ·IATA | AEROSOLS, flammable | |
| · 14.3 Transport hazard class(es) | | |
| · ADR | | |
| · Class | 2 5F Gases. | |
| · Label | 2.1 | |
| | | |
| · IMDG, IATA | | |
| | | |
| · Class | 2.1 | |



Printing date 07.09.2018

Version number 6

Trade name: 4CR 7442 WBS Prefill Spray

| | (Contd. of page |
|--|--|
| · 14.4 Packing group · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | No |
| · Marine pollutant: | INO |
| 14.6 Special precautions for user Danger code (Kemler): | Warning: Gases. |
| · EMS Number: | F-D.S-U |
| · Stowage Code | SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clea of living quarters. |
| · Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacit above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2. |
| · 14.7 Transport in bulk according to Anne | ex II of |
| Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Transport category | 2 |
| • Tunnel restriction code | D |
| · IMDG | |
| \cdot Limited quantities (LQ) | 1L |
| · UN ''Model Regulation'': | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I methanol

· Seveso category P3a FLAMMABLE AEROSOLS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

| Class | Share in % |
|-------|------------|
| Ι | ≥0.1-<2.5 |
| NK | 50-100 |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

GB



Printing date 07.09.2018

Version number 6

Trade name: 4CR 7442 WBS Prefill Spray

| | (Contd. of page |
|------------------|---|
| Relevant ph | 8 |
| | flammable gas. |
| | mmable liquid and vapour. |
| | le liquid and vapour. |
| | gas under pressure; may explode if heated. |
| H301 Toxic | |
| H302 Harm | |
| | tal if swallowed and enters airways. |
| • | ontact with skin. |
| | n contact with skin. |
| H315 Cause | |
| | |
| | rious eye damage. |
| | rious eye irritation. |
| H331 Toxic | |
| H332 Harm | |
| | e respiratory irritation. |
| | e drowsiness or dizziness. |
| | mage to organs. |
| | e damage to organs through prolonged or repeated exposure. |
| | ccording to Regulation (EC) No 1272/2008 |
| The classifie | n of the mixture is generally based on the calculation method using substance data accordi |
| to Regulatio | C) No 1272/2008. |
| Abbreviatio | nd acronyms: |
| | ernational concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning |
| | port of Dangerous Goods by Rail) |
| IATA-DGR: De | ous Goods Regulations by the "International Air Transport Association" (IATA) |
| | l Civil Aviation Organisation Instructions by the "International Civil Aviation Organisation" (ICAO) |
| | éen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internation |
| | ous Goods by Road) |
| | l Maritime Code for Dangerous Goods |
| | Air Transport Association |
| | nonised System of Classification and Labelling of Chemicals Inventory of Existing Commercial Chemical Substances |
| | List of Notified Chemical Substances |
| | tracts Service (division of the American Chemical Society) |
| VOC: Volatile | nic Compounds (USA, EU) |
| | ntration, 50 percent |
| LD50: Lethal a | 50 percent paccumulative and Toxic |
| | nt and very Bioaccumulative |
| | nahle gases – Category 1 |
| Aerosol 1: Aer | · · · · |
| | under pressure – Liquefied gas |
| | nable liquids – Category 2 |
| | nable liquids – Category 3 toxicity – Category 3 |
| | toxicity – Category 5 |
| | prosion/irritation – Category 2 |
| Eye Dam. 1: Se | s eye damage/eye irritation – Category 1 |
| Eye Irrit. 2: Se | eye damage/eye irritation – Category 2 |
| | c target organ toxicity (single exposure) – Category 1 |
| | e target organ toxicity (single exposure) – Category 3 e target organ toxicity (repeated exposure) – Category 2 |
| | ion hazard – Category 1 |
| p . + O 1. Mi | d to the previous version altered. |