



Art.-No.: 6.5122.0033

5122

Glas Primer

Characteristics

4CR 5122 Glas Primer is a black primer specifically designed for the ceramic band on vehicle glass. It ensures the complete protection of the adhesive by creating a barrier against harmful UV rays which can lead to the degradation of the adhesive.

It is also an adhesion promoter.

To be used in conjunction with 4CR 5121 Glas Cleaner/Activator.

Application

The surfaces to be treated must be perfectly clean, dry, dust and grease free.

Application of 5122 can only take place once the thorough cleaning of the bonding area with 5121 Glas Cleaner/Activator has been completed.

- Shake bottle well before application (for at least 1 min.) till the noise of the metal balls contained in the bottle can be heard.
- Apply product using a felt applicator.
- Close immediately after use as product evaporates very quickly.
- Ensure that primer is tack-free dry before proceeding.



Technical Data

Application temperature	+10°C to +35°
Maximum drying time	24h at 23°C and 50% r.h.
Specific gravity	0,95 gr/cc
Minimum drying time	5' at 23°C and 50% r.h.
Curing mechanism	Moisture curing
Odour	Characteristic of solvent
Aspect	Liquid
Colour	Black

Storage and Transportation

5122 can be stored for 9 months in its original packing at 5°- 25°C. The product is flammable. Keep away from heat sources, store in a dry and well-ventilated area in its original packaging. Keep out of the reach of children.