



Art.-No.: 6.5170.1000

5170

Brushable Seam Sealer

Characteristics

4CR 5170 is a one-part, thixotropic, rubber based sealant in solvent for applications by brush. Once extruded, it cures fast to form a high performance, permanently elastic sealing compound.

It does not crack and provides an excellent barrier against dust, water and humidity.

Tech Tip

Ideal for bonding metallic surfaces and for joint filling of the car body such as on flanges and welded parts of front and rear vehicle.

It is also suitable for the inner automobile parts that are not directly exposed to UV rays such as baggage compartment.



Application

Surfaces must be clean, dry, free of water, oil, grease or rust and of sound quality. Remove all loose particles or residues with a jet of compressed air, sandpaper or hard brush. Glass, metal and other non-porous surfaces must be free of any coatings and wiped clean with solvent.

Easily applicable with a soft or hard brush or spatula, can be over-painted with the most used paints available on the market (preliminary compatibility tests advisable).

Technical Data

Dry residue	72 ± 2%
Colour	Grey
Chemical nature	Synthetic rubber in solvent
Density [g/cc]	1,43 ± 0,3

Storage and Transportation

Can be stored for 12 months in its original packing (unopened container) at 5°- 25°C in a cool, dry place. The storage temperature should not exceed 25°C for extended periods of time. Keep away from wet areas, direct sunlight and heat sources.