



Art.-No.: 6.5200.0500

5200

Underbody Protection Bitumen Spray

Characteristics

4CR 5200 Underbody Protection Bitumen Spray is a durable elastic underbody protection based on rubber-bitumen.

Provides a long-term protection against water, salt, corrosion on corners, edges or for repair work.

Tech Tip

- Abrasion resistant, durable elasticity
- Anti-corrosive
- Not overcoatable!
- Excellent anti-noise characteristics

Application

Substrate: The substrate must be clean from rust, grease, and polishing agents and sanded. If necessary primed.

Pretreatment / Cleansing: Pre-cleansing with 4CR Silikonentferner.

Processing Conditions: Can be processed at any temperature.

Do not spray on the motor, gears, brakes etc.

All substrates must be clean, dry and free from grease. Shake can vigorously for approx. 3 mins. prior to use. Spraying distance approx. 20 - 30 cm. Apply several thin layers, with a flash-off period of approx. 3 - 5 Minuten between each coating.

After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.



Technical Data

Colour	black
Content	500 ml
Full hardness	Dry after 5 h / 20°C

Storage and Transportation

The product may not be stored under +10°C and above +30°C the packaging must be protected from direct sunlight and heat. Cool and moisture free stored the product is tenable for a minimum of 2 years in the unopened original packaging.