



Art.-No.: 6.6767.0001
 6.6767.0002
 6.6767.00036.
 6767.0004

6767

Nitrile Gloves Premium

Characteristics

Powder-free nitrile gloves for protection against skin irritation. Ideal for use in laboratories, for paint works, in the mixing areas as well as for small maintenance jobs.

- Protection from unwanted and dangerous substances
- Beaded cuff ensures easy donning and prevent roll down
- Superior strength with better puncture resistance
- Full textured enhances wet and dry grip
- Thinner gauge improves tactile sensitivity
- Custom design enhances comfort and fit
- Provide an alternative solution for individuals who are allergic to natural rubber latex



Tech Tip

- increased solvent resistance
- extremely flexible, perfect fit and excellent comfort

EN 455- 1/2/3

Abrasion resistance - Level 0
 Blade cut resistance - Level 0
 Tear resistance - Level 0
 Puncture resistance - Level 0

EN455-1:2000

Freedom from Holes GI/ 1.5
 (Water Tight Test) GI/ 1.5

EN455-2

EN455-2 : 2009 + A2 : 2013

EN455-III

EN455-3 : 2006
 ASTM D6319-10
 ASTM D6124-06 (2011)

Technical Data

Sizes	M/8 (6767.0001), L/9 (6767.0002), XL/10 (6767.0003), XXL/11 (6767.0004)
CE	CE Type Examination Certificate No. NPFFT- ENW40-BK-240-1.5-NS
Packaging	100 pieces dispensing box
Colour	Black
Thickness Finger (mm)	0.10 +/- 0.02 (Typical value: 0.11 - 0.12)
Thickness Palm (mm)	0.07 +/- 0.02 (Typical value: 0.07 - 0.08)



Art.-No.: 6.6767.0001
6.6767.0002
6.6767.00036.
6767.0004

6767

Storage and Transportation

Storage Condition The gloves shall maintain their properties when stored in a dry condition. Avoid direct sunlight.

The gloves shall have shelf life of 2 years from the date of manufacture with the above storage condition.