



Art.-No.: 6.6907.5091 6.6907.1591  
 6.6907.6191 6.6907.7625  
 6.6907.7691 6.6907.1025  
 6.6907.8091  
 6.6907.1091

**6907**

## Floor Filter G3 (EU3)

### Characteristics

For the separation of paint mist in mixing areas, paint shops and paint spray booths.

Filter class G3 (EU3). Exhaust air ducts, fans and motors are protected from paint deposits.

The colored green side is to identify the dust air side.  
 The low compressibility of the randomly stored glass fibers prevents the medium from being compressed when it is under pressure and promotes high separation efficiency.



### Tech Tip

- Non- flammable according to DIN 4102
- Tested according to DIN EN 779
- Temperature resistant up to max. 180 ° C
- Silicone-free and free of paint-damaging substances

### Dimensions

- 6.6907.5091 - 50 cm x 91 m
- 6.6907.6191 - 61 cm x 91 m
- 6.6907.7691 - 76 cm x 91 m
- 6.6907.8091 - 80 cm x 91 m
- 6.6907.1091 - 100 cm x 91 m
- 6.6907.1591 - 150 cm x 91 m
- 6.6907.7625 - 76 cm x 25 m
- 6.6907.1025 - 100 cm x 25 m

### Technical Data

Roll length	25 m, 91 m
Roll width	50 cm, 61 cm, 76 cm, 80 cm, 100 cm, 150 cm, 76 cm,
Material thickness	ca. 75mm
Nominal volume flow	2500-6300 m <sup>2</sup> /h/m <sup>2</sup>
Degree of paint separation	95 %
pressure difference	4 - 10 Pa
Recommended final pressure differential	80 Pa

### Storage and Transportation

Store dry