Technical Data Sheet Revised: 2020-05-08 | 1/2



**Art.-No.:** 6.7420.0401 6.7420.0402 6.7420.0403 6.7420.0404

**7420** 

# Rallye Spray black silk-mat

## Characteristics

7420 Rallye Spray is a fast drying car refinishing paint. The product is weather resistant and lightfast.

Especially suited for fast and simple repair work on cars and other vehicles.

### Available in:

7420.0401 black matt 7420.0402 glossy black 7420.0404 black silk matt

7420.0403 glossy white

#### Tech Tip

- Fast drying, weather resistant.
- Good hiding power, good adhesion.
- Lead-free, lightfast.

## Application

Substrate: Fully hardened and sanded old paint work, thoroughly dry 1K and 2K Filler materials.

Pretreatment / Cleansing: Precleansing with 4CR silicone remover.

Processing conditions from  $+15^{\circ}$ C to  $+25^{\circ}$ C and upto 80% relative air humidity.

All substrates must be clean, dry and free from grease.

Shake can vigorously for approx. 3 mins. prior to use. Spraying distance approx. 20 - 30 cm.

Apply several thin layers

3 - 4 coats, dry film thickness of 40 - 60  $\mu m$ 

Flash-off time of approx. 3 - 5 Minuten between each coating.

After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

## **Technical Data**

Colour / Grade of Gloss black mat, Black glossy, Black silk, White glossy

Dust-dry after approx. 10 Min. Set to touch after approx. 1- 2 h.

Full hardness after 24 h.



Technical Data Sheet Revised:2020-05-08 | 2/2



**7420** 

# Storage and Transportation

Can be stored for at least 2 years in the closed original container.