



Art.-No.: 6.7435.0400

**7435**

## Clearcoat Spray

---

### Characteristics

---

4CR 7435 clear coat spray is a colorless, non-yellowing protective coating based on acrylic.

Not suitable for use on bare metal, iron, brass, copper and aluminum.

- lightfast and resistant to yellowing
- good adhesion and gloss retention
- weatherproof, protects against environmental influences, Oxidation and change in color or gloss

---

### V.O.C. Value

---

EU limit value for the product (Cat. B / e): 840 g / l (2007)  
This product contains a maximum of 700 g / l VOC

---

### Tech Tip

---

Spray first a mist coat, after approx 1-2 min then beginn applying thicker coats. 2-3 coats.

After use, turn the spray can upside down and spray the nozzle empty, this prevents the paint material in the nozzle head from drying out.





Art.-No.: 6.7435.0400

**7435**

---

## Application

---

Processing conditions: From + 10 ° C and up to 80% relative humidity.

Not suitable for the use on bare iron, brass, copper and aluminum.

For the use on hardened or sanded old paintwork as well as on dried 1K and 2K filler materials.

The surface must be clean, dry and free of grease. Sand surfaces. Remove uncured old paintwork or primers.

- Shake the spray can well for about 3 minutes before use.
- The spraying distance should be approx. 20 - 30 cm.
- Apply 2 - 3 coats, dry film thickness 50 µm.
- Flash-off time of approx. 3-5 minutes between coats.

Drying time at 20 ° C

Dust dry after approx. 5 - 10 min.

Set to touch after approx. 20 - 30 min.

Assemblability after about 2 hours

---

## Technical Data

---

Colour	Farblos
Film thickness	50 µm
Flash off time	Approx: 3-5 minutes between coats.
Pot life at 20°C	unlimited
Size	400 ml

---

## Storage and Transportation

---

Store dry and frost-free.

Can be stored for at least 2 years in the original closed container.