



Art.-No.: 6.7440.0400

7440

Prefill Spray

Characteristics

4CR 7440 Prefill Spray is individually produced in quality and colour. By taking care of the specific application procedures of each product, high quality surface finishes equal to the product features will be achieved.

The trader is liable for the final product!

- The paint is filled into the aerosol using an aerosol filling machine.
- Equipped with an adjustable FAN-sprayhead.
- Customised solutions for most areas of application.

V.O.C. Value

EC limiting value for the product (cat. B/e): 840 g/l (2007)
 This product contains max. 840 g/l VOC [7.01 lbs/gal]

Application

Substrate:

Fully hardened and abraded old substrates.
 Thoroughly dry 1K-filler and 2K-filler materials.

Pretreatment / Cleansing:

Pre-cleansing with 4CR silicone remover 0610.

Preparation: Shake can vigorously until the mixing balls move freely!

Application: Spray to test - Spraying distance approx. 20 - 30 cm.
 Depending on the final product.

Flash-off: Depending on the final product.

After use: Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying Times:

Depending on the final product

Processing Conditions:

From +10°C and up to 80% relative air humidity.

Technical Data

Colour / Grade of Gloss Depending on the final product

Storage and Transportation

In tightly closed original containers at least 2 years shelf life.

