



Art.-No.: 6.7442.0400

7442

WBS Prefill Spray

Characteristics

4CR 7442 WBS Prefill Spray is especially suitable for many waterbased paint systems. Pre-charged with a mixture of propellant and other additives.

The trader is liable for the final product!

- The paint is filled into the aerosol using an aerosol filling machine.
- Equipped with an adjustable FAN-sprayhead.
- Customised solutions for most areas of application.

V.O.C. Value

EC limiting value for the product (cat. B/e): 840 g/l (2007)
 This product contains max. 840 g/l VOC [7.01 lbs/gal]

Application

Substrate:

- Thoroughly cured 2K-primers and/or 2K-fillers.
 - 1K-primers and/or 1K-fillers (only if overcoatable with 1K-waterbased paints).
 - Thoroughly cured and abraded old layers of paint (only if re-coatable with 2K-paint).
- It is advised to spray a sample first!

Pretreatment / Cleansing:

Abrade substrate and cleanse with 4CR silicone remover.

Preparation: Shake can vigorously until the mixing balls move freely!

Application: Spray to test - Spraying distance approx. 20 - 30 cm.

Depending on the final product.

Flash-off: Depending on the final product.

After use: Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying Times:

Depending on the final product

Processing Conditions:

From +10°C and up to 80% relative air humidity.

Technical Data

Colour / Grade of Gloss Depending on the final product

Storage and Transportation

In tightly closed original containers at least 2 years shelf life.
 Shelf Life (Final product): 1 week - 2 weeks (depending on the system and tinters)

