Technical Data Sheet Revised:2020-05-08 | 1/1



Art.-No.: 6.7480.0400

7480

Adhesive Spray

Characteristics

High quality glue for both permanent and temporary adhesion. Suitable to glue paper, cardboard, wood, cork, leather, textile and various types of plastic.

Tech Tip

- Suitable to glue large surfaces
- Fast drying
- User-friendly
- Spray pattern about 10 centimetre wide

Application

The surface should be clean, dry and free of grease.

The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol.

The Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the adhesive spray in an equal layer.

For a permanent adhesion treat both parts to be glued, allow to dry 15 to 20 minutes and firmly press together.

For a temporary adhesion treat one of the parts to be glued, allow to dry for 5 to 10 minutes, and firmly press together.

When treating porous surfaces, apply several layers.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Technical Data

Contents 400 ml

Basis Synthetic resin

VOC-content Approximately 83% w/w Colour Transparent white

Relative density at 20°C 0,75 g/ml Yield 1,2 g/sec Vapour pressure at 20°C 3 to 4 bar Heat resistant To 80°C

Storage and Transportation

Keep dry an frost-protected. At least 2 years shelf life.

